



LABORATORIES

Issue Date 11-Apr-2015

Revision Date 16-June-2015

Version 1

SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Product Name United 117 STAINLESS STEEL CLEANER AND POLISH

Other means of identification

SDS# UNITED 117

Recommended use of the chemical

And restrictions on use

Recommended use Professional Strength Metal Polish
Uses Advised Against For industrial and institutional use only.

Details of the supplier of the safety data sheet

Company Name

United Laboratories, Inc.
320 37th Avenue
St. Charles, IL 60174
www.unitedlabsinc.com
www.unitedlabsinc.ca

Emergency telephone number

Emergency Telephone 800-323-2594 (to reorder)
INFOTRAC 1-800-535-5053 (North America)
1-352-323-3500 (International)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable Aerosols	Category 1
Serious Eye damage/eye irritation	Category 2A
Aspiration hazard	Category 1
Specific target organ toxicity, single exposure	Category 3 narcotic effects

Label elements

Emergency Overview

Danger

Hazard statements

Extremely flammable aerosol. My be fatal if swallowed and enters airways. Causes serious eye irritation. May cause drowsiness or dizziness.

**Appearance** Colorless**Physical state** Liquid**Odor** Lemon/Solvent**Prevention**

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye/face protection.

Response

If inhaled: Remove individual to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and able to do so. Continue rinsing. If swallowed: Immediately call a poison center or physician if you feel unwell. Do not induce vomiting. If eye irritation persists: get medical attention.

Storage

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Keep container tightly closed. Store in a well-ventilated place.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

Not classified.

Supplemental information

51.75% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 51.75% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
Acetone	67-64-1	10-20	*
Petroleum distillates, hydrotreated light	64742-47-8	20-40	*
Propane	74-98-6	10-20	*
Methyl Acetate	79-20-9	2.5-10	
Other components below reportable levels	-	20-40	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures**Skin Contact**

Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continuing rinsing. If eye irritation persist: Get medical advice / attention.

Inhalation Remove individual to fresh air and keep at rest in a position comfortable for breathing. Call a poison control or physician if you feel unwell.

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis.

Most important symptoms and effects, both acute and delayed

May cause drowsiness and dizziness. Irritation of eyes and mucous membranes.

Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep individual under observation. Ensure the medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Powder. Alcohol resistant foam. Dry chemicals. Carbon Dioxide.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed space, SCBA. If there is no risk, move containers from fire area. Containers should be cooled with water to prevent vapor pressure build up.

Specific Methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. In the event of fire and/or explosion do not breathe fumes.

General fire hazards

Extremely flammable aerosol.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid breathing mist or vapor. Ventilate closed spaces before entering them. Local authorities should be advised in significant spillages cannot be contained. For personal protection, see Section 8 of the SDS.

Environmental precautions

Environmental precautions

Avoid release into the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

Methods and material for containment and cleaning up

Methods for containment Refer to attached SDS and/or instructions for use. Prevent further leakage or spillage if safe to do so. Move the container to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep combustibles (wood, oil, paper, etc.) away from spilled material. Stop leak if you can do so without risk. Isolate area until gas has dispersed. Collect spillage.

Methods for cleaning up Move the container to a safe and open are if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Prevent entry into waterways, sewer, basements or confined areas. Flush area with water, after product has been cleaned. For waste disposal see Section 8 of SDS.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Pressurized container: Do not pierce or burn, even after use. Do not smoke while using or until sprayed surface is thoroughly dry. Keep away from heat, sparks, flame and other sources of ignition. Do not spray on naked flame or any other incandescent material. Equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not re-use empty containers. Use only in ventilated areas. Avoid breathing in vapor or mist. Avoid contact with eyes. Avoid prolonged exposure. Observe good industrial hygiene practices. Wash hands thoroughly after handling. Avoid release into environment.

Conditions for safe storage, including any incompatibilities

Storage Conditions Store locked up. Pressurized container. Do not puncture, incinerate or crush. Do not handle or store near flame, heat and sources of ignition. Avoid exposure to direct sunlight, exceeding 50°C/122°F. This material can accumulate static charge which may cause spark and become an ignition source. Level 3 Aerosol

Incompatible materials Store away from incompatible materials (see Section 10 of the SDS).

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines No Exposure limits noted for ingredient(s).

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone 67-64-1	STEL: 750 ppm TWA: 500 ppm	PEL: 2400 mg/m3 PEL: 1000 ppm	TWA: 590 mg/m3 TWA: 250 ppm
Propane 74-98-6	-	PEL: 1800 mg/m3 PEL: 1000 ppm	TWA: 1800 mg/m3 TWA: 1000 ppm
Methyl Acetate 79-20-9	STEL: 250 ppm TWA: 200 ppm	PEL: 610 mg/m3 PEL: 200 ppm	STEL: 760 mg/m3 STEL: 250 ppm TWA: 610 mg/m3 TWA: 200 ppm

NIOSH IDLH Immediately Dangerous to Life or Health

Biological limit values Acetone (67-64-1) 50 mg/l – Urine specimen.

Appropriate engineering controls

Engineering Controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear eye/face protection. Wear safety glasses with side shields or goggles.
Skin and body protection	Wear protective gloves. Wear appropriate chemical resistant clothing.
Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.
General Hygiene	When using do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Aerosol
Appearance	Clear
Color	Colorless
Odor	Lemon/Solvent

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No Information available.	
Specific Gravity	No information available.	
Percent volatile	No information available.	
Viscosity	No Information available.	
Melting point/freezing point	No Information available.	
Flash point	-156.0°F (104.4°C) estimated	
Boiling point and Boiling range	No information available.	
Evaporation rate	No information available.	
Flammability (solid, gas)	No information available.	
Upper flammability limit:	No information available.	
Lower flammability limit:	No information available.	
Vapor pressure	43-66 psig @70F estimated	
Vapor density	No Information available.	
Relative density	No information available.	
Water solubility	No information available.	
Partition coefficient	No information available.	
Auto-ignition temperature	No information available.	
Decomposition temperature	No information available.	
VOC (weight %)	29.7% estimated	

10. STABILITY AND REACTIVITY

Reactivity
This product has strong oxidizing agents.

Chemical stability
Material is stable at normal conditions.

Possibility of Hazardous Reactions
Hazardous polymerization does not occur.

Conditions to avoid
Avoid temperatures exceeding the flash point. Avoid heat, spark, open flames and other ignition sources.

Hazardous Decomposition Products

No hazardous decomposition products are known.

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure****Product Information**

Inhalation	May be fatal if swallowed and enters airways. Prolonged inhalation may be harmful. Narcotic effects.
Eye contact	May cause serious eye irritation.
Skin Contact	No information available.
Ingestion	May be fatal if swallowed and enters airways.
Symptoms related to the physical, chemical and toxicological characteristics	Causes serious eye irritation. Symptoms of overexposure may be headache, dizziness, tiredness, nausea or vomiting.

Information on toxicological effects

Acute toxicity Narcotic effects. Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

Chemical Name	Dermal LD50	Oral LD50	Inhalation LC50
Methyl Acetate 79-20-9	4997 mg/kg (Rat)	3.7 g/kg (Rabbit)	3961 mg/l/ 4 hours (Rat)
Acetone 67-64-1	20000 mg/kg (Rabbit) 20 ml/kg (Rabbit)	5340 mg/kg (Rabbit)	76 mg/l, 4 hours (Rat)
Propane 74-98-6	-	-	>1442 mg/l, 15 minutes 658 mg/l/ 4 hours (Rat)

*Estimates for product may be based on additional component data not shown.

Skin/Eye irritation	Prolonged skin contact may cause mild skin irritation. Causes serious eye irritation.
Sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No information available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP or OSHA.
Reproductive toxicity	No expected to cause reproductive or developmental effects.
STOT - single exposure	Narcotic effects. May cause drowsiness and dizziness.
STOT - repeated exposure	No Information available.
Aspiration hazard	May be fatal if swallowed and enters airways.
Chronic effects	Prolonged inhalation may be harmful.

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Toxic to aquatic life with long lasting effect. Accumulation in aquatic organisms is expected.

Persistence and degradability

No Information available.

Bioaccumulation

No Information available.

Chemical Name	Partition coefficient
Acetone 67-64-1	-0.24
Propane 74-98-6	2.36
Methyl Acetate 79-20-9	0.18

Other adverse effects No other adverse environmental effects (e.g., ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Collect or dispose in sealed containers and licensed waste disposal site. Contents under pressure. Do not puncture or incinerate. Do not drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Disposal should be in accordance with applicable regional, national and local laws and regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

US RCRA Hazardous Waste U List: Reference Acetone (67-64-1) U002

Waste from residues/unused products Dispose in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner. (See Disposal Instructions).

Contaminated packaging Do not reuse container. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. TRANSPORT INFORMATION

This product meets the exception requirements of Section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity-ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/2020 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

DOT

UN/ID No. UN1950
Proper shipping name Aerosols, flammable
Transport hazard class(es) 2.1
Label(s) None
Special provisions N82
Packing exceptions 306

IATA

UN/ID No. UN1950
UN proper shipping name Aerosols, flammable
Transport hazard class(es) 2.1
Label(s) 2.1
ERG code 10L

IMDG

UN/ID No.	UN1950
Proper shipping name	Aerosols, flammable
Transport hazard class	2.1
Label(s)	None

Environmental Class

Marine Pollutant	Yes. Environmental hazards-Yes
------------------	--------------------------------

15. REGULATORY INFORMATION**International Inventories**

Australia, United States, Canada, China, Europe, Japan and Puerto Rico-Yes*
 Europe, Korea, New Zealand and Philippines-No

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory-No regulated.

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List-No

*A Yes indicates that all components of this product comply with the inventory requirements administered by the governing county(s). A No indicates that one or more components of the product are no listed or exempt from listing on the inventory administered by the governing country(s).

US Federal Regulations**SARA 302 Extremely hazardous substance**

None.

Superfund Amendments and Reauthorization Act of 1986

Acute health hazard	Yes
Delayed hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	Yes
Reactive Hazard	No

SARA 313 (TRI reporting)

None.

SARA 311-312 Hazardous chemical

None.

CERCLA

This material, as supplied, does contain a substance regulated as a hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material. Acetone (67-64-1) Listed.

CAA (Clean Air Act) Section 112 Hazardous Air Pollutants (HAPs) List – Not regulated.

CAA (Clean Air Act) Section 112(r) Accidental Release Prevention (40 CFR 68.130) – Propane (74-98-6)

SDWA (Safe Drinking Water Act) – Not Regulated.

DEA (Drug Enforcement Administration). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number – Acetone (67-64-1-1) 6532

DEA, List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c)) – Acetone (67-64-1) 35% WV

DEA, Exempt Chemical Mixtures Code Number – Acetone (67-64-1) 6532

FDA (Food and Drug Administration) Not Regulated.

US State Regulations

California Proposition 65

This product is not known to contain any chemicals listed as carcinogens or reproductive toxins.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Pennsylvania
Methyl Acetate (79-20-9)	-	X
Propane 74-98-6	X	X
Acetone 67-64-1	X	X

16. OTHER INFORMATION

NFPA	Health hazards -	Flammability -	Instability -	Physical and Chemical Properties -
HMIS	Health hazards *1	Flammability 3	Physical hazards 0	Personal protection x

Issue Date 11-Apr-2015
Revision Date 16-June-2015

Revision Note
No Information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet