

Revision Number: 004.0 Issue date: 01/25/2016

### 1. PRODUCT AND COMPANY IDENTIFICATION

**Loctite Power Grab Ultimate** IDH number: **Product name:** 1989550

**Construction Adhesive** 

Product type: Adhesive

Restriction of Use: None identified Company address:

Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

Region: **United States** 

Contact information:

Telephone: +1 (800) 624-7767

MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

### 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

WARNING: ABRASION COULD RELEASE RESPIRABLE PARTICLES OF SILICA

QUARTZ, A CANCER HAZARD BY INHALATION. NORMAL USE OF THIS

PRODUCT CAUSES NO SUCH RELEASE.

CAUSES SKIN IRRITATION.

CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A

#### PICTOGRAM(S)



### **Precautionary Statements**

Prevention:

Wash affected area thoroughly after handling. Wear protective gloves, eye protection, and face

protection.

Response:

IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical attention. If eve irritation persists: Get medical attention. Take off

contaminated clothing.

Storage: Not prescribed Disposal: Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

IDH number: 1989550 Product name: Loctite Power Grab Ultimate Construction Adhesive Page 1 of 6

Hazardous Component(s)	CAS Number	Percentage*	
Limestone	1317-65-3	60 - 100	
Phthalate Ester	Proprietary	10 - 30	
Silane derivative	Proprietary	1 - 5	
Fatty acid	Proprietary	1 - 5	
3-(Trimethoxysilyl)propylamine	13822-56-5	0.1 - 1	
Quartz (SiO2) respirable particulates (RCS) >=10%	14808-60-7	0.1 - 1	

<sup>\*</sup> Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

Exposure to moisture during cure will release 1-2% methanol.

# 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Skin contact: Wash with soap and water. If skin irritation persists, call a physician. Wipe off

paste with paper towel or cloth.

Eye contact: Flush with copious amounts of water, preferably, lukewarm water for at least

15 minutes, holding eyelids open all the time. If symptoms develop and

persist, get medical attention.

Ingestion: Do not induce vomiting. If a person feels unwell or symptoms of skin irritation

appear, consult a physician.

Symptoms: See Section 11.

### 5. FIRE FIGHTING MEASURES

Extinguishing media: carbon dioxide, foam, powder, water spray jet, fine water spray

Special firefighting procedures: Wear protective equipment. Wear self-contained breathing apparatus.

Unusual fire or explosion hazards: None identified.

IDH number: 1989550

Hazardous combustion products: Carbon dioxide Carbon monoxide.

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways.

Clean-up methods: Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

Store in a partly filled, closed container until disposal. Spilled material will solidify. Scrape up as much material as possible. Maintain good ventilation for

large spills.

## 7. HANDLING AND STORAGE

**Handling:** Do not wear contact lenses. Avoid contact with eyes, skin and clothing. Keep

out of the reach of children. Protect from moisture. Use only with adequate

ventilation.

Storage: For safe storage, store between 20 °C (68°F) and 45 °C (113°F)

Store in a cool, dry area. Avoid moisture.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone	10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Phthalate Ester	None	None	None	None
Silane derivative	None	None	None	None
Fatty acid	10 mg/m3 TWA	None	None	None
3-(Trimethoxysilyl)propylamine	None	None	None	None
Quartz (SiO2) respirable particulates (RCS) >=10%	0.025 mg/m3 TWA Respirable fraction.	0.3 mg/m3 TWA Total dust. 2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable.	None	None

Engineering controls: Local exhaust ventilation is recommended when general ventilation is not

sufficient to control airborne contamination below occupational exposure

limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

**Eye/face protection:** Safety goggles or safety glasses with side shields.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin

contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Paste, Solid Color: White to tan Odor: alcohol-like Odor threshold: Not available. pH: Not available. Vapor pressure: Not available. Boiling point/range: Not available. Melting point/ range: Specific gravity: Not available. 1.70 - 1.72 Vapor density: Heavier than air.

Flash point: 107 °C (224.6 °F) Seta closed cup

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Autoignition temperature:

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

Not available.

Not available.

Insoluble

Not available.

IDH number: 1989550 Product name: Loctite Power Grab Ultimate Construction Adhesive Page 3 of 6

VOC content: 2.73 %; 48.13 g/l (by weight, calculated using CARB method; g/L less water,

less exempts calculated using SCAQMD method)

Viscosity: 1,800 - 2,200 mPa.s Decomposition temperature: Not available.

### 10. STABILITY AND REACTIVITY

**Stability**: Stable under normal conditions of storage and use.

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

IDH number: 1989550

Methanol is liberated slowly upon exposure to moisture.

Incompatible materials: Oxidizing agents.

Reactivity: Not available.

Conditions to avoid: Exposure to moisture.

## 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Inhalation, Skin contact, Eye contact

#### Potential Health Effects/Symptoms

Inhalation: May be harmful if inhaled. Methanol is released during application and cure, which may affect

the nervous system causing dizziness, headache or nausea.

**Skin contact:** Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis.

**Eye contact:** Vapors may irritate eyes. Contact with eyes will cause irritation. **Ingestion:** Harmful if swallowed. Not expected under normal conditions of use.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Limestone	None	Nuisance dust	
Phthalate Ester	Oral LD50 (RAT) = 64,000 mg/kg Dermal LD50 (RABBIT) = > 3,160 mg/kg Inhalation LC50 (RAT, 4 h) = > 12.54 mg/l	Irritant, Allergen	
Silane derivative	None	Irritant, Allergen	
Fatty acid	Oral LD50 (RAT) = 4.6 g/kg	Irritant	
3-(Trimethoxysilyl)propylamine	None	Irritant, Allergen	
Quartz (SiO2) respirable particulates (RCS) >=10%	None	No Data	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Limestone	No	No	No
Phthalate Ester	No	No	No
Silane derivative	No	No	No
Fatty acid	No	No	No
3-(Trimethoxysilyl)propylamine	No	No	No
Quartz (SiO2) respirable particulates (RCS) >=10%	Known To Be Human Carcinogen.	Group 1	No

## 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

**Hazardous waste number:** It is the responsibility of the user to determine if an item is hazardous as

defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics

Leaching Procedure (TCLP) 40 CFR 261.20-24.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:
Not regulated
None
None
None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None

Identification number:

Packing group:

None

### 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA Section 313:

None above reporting de minimis.
Delayed Health, Immediate Health
None above reporting de minimis.

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

**Canada Regulatory Information** 

IDH number: 1989550

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other

components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities.

Please contact Regulatory Affairs for additional details.

### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 3, 8, 11

Prepared by: Mary Ellen Roddy, Sr. Regulatory Affairs Specialist

**Issue date:** 01/25/2016

IDH number: 1989550

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.