

MATERIAL SAFETY DATA SHEET: YIELD AEROSOL

Section I - General Information

(000000-000000- - 5068)

Date of Issue: 12/21/2007 12:00:00 AM
Chemical Name & Synonyms: N/A

Chemical Family: Petroleum distillate mixture
Manufacturer Name: CHEMSEARCH DIV. OF NCH CORP.
Manufacturer Address: BOX 152170 IRVING, TX 75015

Prepared By: M MCDOWELL/CHEMIST

Product Code Number: 5068

Supercedes: 12/21/2007 12:00:00 AM
Trade Name & Synonyms: YIELD AEROSOL
Formula is a mixture: [V]

Section II - Hazardous Ingredients

THE HAZARDS PRESENTED BELOW ARE THOSE OF THE INDIVIDUAL COMPONENTS

Table with 6 columns: Chemical Name (Ingredients), Hazard, TLV, PEL, STEL, CAS #. Lists various petroleum products and their associated hazards and exposure limits.

Section III - Physical Data

Boiling Point (°F):160-203
Vapor Pressure (mm Hg):1546
Vapor Density (Air=1):1.7
pH @ 100% :N/A
% Volatile by Volume:75
H2O Solubility:Negligible
Specific Gravity (H2O=1):0.84
Color:Amber-dark amber
Odor:Petroleum/vinegar
Clarity:Transparent
Evaporation Rate (BuAc=1):24.8
Viscosity:Non-Viscous

Section IV - Fire and Explosion Hazard

Flash Point: <80°F
Flammable Limits: Product mixture
LEL: 0.5%
Method Used: Seta-flash
UEL: 11.5%
Aerosol Level (NFPA 30B): 3

Extinguishing Media: [V] Foam, [ ] Alcohol Foam, [V] CO2, [V] Dry Chemical, [V] Water Spray, [ ] Other

NFPA 704 Hazard Rating: 4-Extreme Health: 2, 3-High Flammability: 4, 2-Moderate Instability: 0, 1-Slight Special: 0-Insignificant

Special Fire Fighting Procedures: Firefighters should wear a self-contained breathing apparatus and full protective gear.
Unusual Fire and Explosion Hazards: Vapors are heavier than air and may travel to distant and/or low-lying sources of ignition and flashback.

Section V - Health and Hazard Data

Threshold Limit Value: Not Established for Mixture. See Section II.

Effects of Overexposure:

Acute: (Short Term Exposure)

EYE CONTACT: Causes irritation seen as stinging, tearing, redness, and a burning sensation.
SKIN CONTACT: Causes irritation seen as itching and redness.
INHALATION: May cause respiratory irritation seen as coughing and sneezing.
INGESTION: May cause irritation with possible nausea, vomiting, and diarrhea.

Chronic: (Long Term Exposure)

This product has a narcotic and Central Nervous System depressive effect. May cause Kidney and Liver congestion in high concentrations.
TARGET ORGANS: Central nervous system, heart, liver, lungs, and kidneys. The primary routes of exposure are skin and eye contact.

Primary Routes of Entry

<input checked="" type="checkbox"/> Inhalation	<input type="checkbox"/> Ingestion	<input checked="" type="checkbox"/> Absorption
--	------------------------------------	--

**Emergency First Aid Procedures:**

**Inhalation:**  
Remove from the area to fresh air. Seek medical attention if respiratory irritation develops or if breathing becomes difficult.

**Eye Contact:**  
Rinse the eyes with water. Remove any contact lenses and continue flushing with plenty of water for several minutes. Seek medical attention if irritation develops.

**Skin Contact:**  
Wash affected areas with large amounts of soap and water for 15 minutes. Remove contaminated clothing and shoes. Seek medical attention if irritation persists. Wash clothing and clean shoes before re-use.

**Ingestion:**  
Give 3 to 4 glasses of water, but DO NOT induce vomiting. If vomiting occurs, give fluids again. Get immediate medical attention. Do not give anything by mouth to an unconscious or convulsing person.

**Notes to Physician:**  
Ingestion and subsequent vomiting of this product can lead to aspiration of the product into the lungs which can cause damage and may be fatal. Depending on the amount ingested and retained as well as the toxicity of the product, gastric lavage should be considered. Keep patient's head below hips to prevent pulmonary aspiration. If comatose, a cuffed endotracheal tube will prevent aspiration. In the event of injection in underlying tissue, immediate treatment should include extensive incision, debridement and saline irrigation. Inadequate treatment can result in ischemia and gangrene. Early symptoms may be minimal.

**Section VI - Toxicity Information**

Product Contains Chemicals Listed as Carcinogen or Potential Carcinogen By:

<input type="checkbox"/> IARC	<input type="checkbox"/> NTP	<input type="checkbox"/> OSHA	<input type="checkbox"/> ACGIH	<input type="checkbox"/> Other
-------------------------------	------------------------------	-------------------------------	--------------------------------	--------------------------------

ALIPHATIC PETROLEUM DISTILLATES  
 ORL-RAT LD<sub>50</sub>: >5,000 mg/kg 3.  
 SKN-RBT LD<sub>50</sub>: >3,160 mg/kg 3.  
 IHL-RAT LC<sub>50</sub>: >5.2 mg/L/4 hr 5.  
 SKN-RBT: Moderate irritation 3.  
 EYE-RBT: Mild irritation 3.

Similar materials were administered orally 5 days/week to male and female rats at 100, 500 or 1000 mg/kg for 13 weeks. An additional group was dosed with 100 mg/kg for 13 weeks followed by a 4-week recovery period. No mortalities or clinical effects were observed. Liver and kidney weights for the 500 and 1000 mg/kg exposure groups were significantly increased. After the 4-week recovery period, there were no differences in organ weights. 3.

Animal data suggest that slight anemia, adaptive liver changes, and kidney toxicity may be caused by repeated overexposure to some similar solvents. The significance of this to humans is unknown. 3.

Hydrocarbon mists derived from highly refined petroleum distillates are reported to have low acute and sub-acute toxicities in animals. Effects from single and short-term repeated exposures to high concentrations well above applicable workplace exposure levels include lung inflammatory reaction, lipoid granuloma formation, and lipoid pneumonia. In acute and sub-acute studies involving exposures to lower concentrations at or near current work place exposure levels produced no significant toxicological effects. In long term studies (up to two years) no carcinogenic effects have been reported in any animal species tested. These petroleum distillates are severely hydrotreated, severely solvent extracted, and/or processed by mild hydrotreatment and extraction. For this reason, they are not classified as cancer hazards. 3.

ETHYL ACETATE  
 EYE-HMN SDT: 400 ppm 4.  
 IHL-HMN TCLo: 400 ppm 4.  
 ORL-RAT LD<sub>50</sub>: 5,620 mg/kg 3.  
 IHL-RAT LC<sub>50</sub>: 16,000 ppm/6h 3.  
 SKN-RBT LD<sub>50</sub>: >20 mL/kg 4.  
 SKN-RBT LS<sub>50</sub>: >18,000 mg/kg 3.  
 INH-RAT LC<sub>50</sub>: 200 gm/m<sup>3</sup> 4.

SODIUM SULFONATE  
 ORL-RAT LD<sub>50</sub>: >5,000 mg/kg 3.  
 SKN-RAT LD<sub>50</sub>: >2,000 mg/kg 3.

**HYDROTREATED LIGHT NAPHTHENIC PETROLEUM DISTILLATE**

ORL-RAT LD<sub>50</sub>: >5 g/kg 3.  
 SKN-RBT LD<sub>50</sub>: >3 g/kg 3.  
 SKN-RBT IRRITATION <0.5/8.0; no appreciable effect 3.  
 EYE-RBT IRRITATION <15/110; no appreciable effect 3.

**PROPANE**

IHL-LC<sub>50</sub> >40% by volume 4.

**N-BUTANE**

IHL-RAT LC<sub>50</sub>: 658 g/m<sup>3</sup>/4h 3.

Human volunteers exposed repeatedly to gases of similar hydrocarbon mixtures ranging from 250 to 1000 ppm exhibited no cardiac or pulmonary function abnormalities. 3.

**SYNTHETIC ISOPARAFFINIC HYDROCARBON (<3% DMSO extractables)**

IHL-RAT LC<sub>50</sub>: >290 ppm 3.ORL-RAT LD<sub>50</sub>: >10 g/kg 3.SKN-RBT LD<sub>50</sub>: >3 g/kg 3.

SKN SENSITIZER: no 3.

SKN IRRITATION: slight 3.

EYE IRRITATION: slight 3.

This hydrocarbon was administered orally 5 days/week to male and female rats at 100, 500 or 1000 mg/kg for 13 weeks. An additional group was dosed with 100 mg/kg for 13 weeks followed by a 4-week recovery period. No mortalities or clinical effects were observed. Liver and kidney weights for the 500 and 1000 mg/kg exposure groups were significantly increased. After the 4-week recovery period, there were no differences in organ weights. 3.

### Section VII - Reactivity Data

**Stability**
 Stable                       Unstable
**Conditions to Avoid:**

Avoid heat, hot surfaces, sparks, and open flames.

**Hazardous Polymerization**
 Will not occur                       May occur
**Conditions to Avoid:**

N/A

**Incompatibility (Materials to Avoid):**

Strong oxidizing agents such as Chlorine bleach and concentrated Hydrogen Peroxide; Chlorosulfonic Acid, Lithium Aluminum Hydride, 2-Chloromethylfuran, Lithium Tetrahydroaluminate, Oleum, Potassium T-Butoxide, Nitric Acid, Perchloric Acid, Chromium Trioxide, Chlorosulfonic Acid, Silica Gel, Alumina, Nitrates, Amines, strong Acids and Bases.

**Hazardous Decomposition Products:**

Oxides of Carbon, Potassium, and, Nitrogen; Aldehydes, Molybdenum, alkylmercaptans, dialkylsulfides, and Hydrogen Sulfides.

### Section VIII - Spill Or Leak Procedures

**Steps to be Taken if Material is Released or Spilled:**

Due to the nature of the packaging, a large spill is unlikely. For a small spill, absorb with a damp cloth and rinse area into a sanitary sewer. Use care as spills may be slippery.

**Waste Disposal Method(s):**

Dispose of in accordance with all Federal, state, and local regulations. Typical disposal is to wrap the empty aerosol container in several layers of newspaper and dispose of in the trash. Aerosol recycling programs are available in many areas. Do not puncture or incinerate this container.

**Neutralizing Agent:**

N/A

### Section IX - Special Protection Information

**Required Ventilation:**

Local ventilation is recommended to control exposure from operations that can generate excessive levels of mists or vapors. Local ventilation is preferred, because it prevents dispersion into work areas by controlling it at its source.

**Respiratory Protection:**

Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2-1992). For concentrations above the TLV and/or PEL but less than 10 times these limits, a NIOSH approved half-facepiece respirator equipped with appropriate chemical cartridges may be used. For concentrations greater than 10 times the TLV and/or PEL, consult the NIOSH respirator decision logic found in publication No. 87-116 or ANSI Z88.2-1992.

**Glove Protection:**

Neoprene or nitrile rubber gloves should be worn. Ensure compliance with OSHA's personal protective equipment (PPE) standard for hand protection, 29 CFR 1910.138.

**Eye Protection:**

Safety glasses with side shields if the method of application presents the likelihood of eye contact. Ensure compliance with OSHA's Personal Protective Equipment (PPE) standard for eye and face protection, 29 CFR 1910.133.

**Other Protection:**

Wear protective clothing when handling. Wash clothing and clean shoes before re-use. A safety shower and an eyewash station should be available.

### Section X - Storage and Handling Information

**Storage Temperature**

Max: 120°F                      Min: 35°F

**Storage Conditions**
 Indoors                       Outdoors                       Heated                       Refrigerated
**Precautions to be Taken in Handling and Storing:**

Use with caution around heat, sparks, pilot lights, static electricity, and open flame.

**Other Precautions:**

Keep out of reach of children. Read the entire label before using the product. Follow the label directions.

### Section XI - Regulatory Information

Chemical NameCAS NumberUpper % Limit

None.

# MATERIAL SAFETY DATA SHEET: YIELD AEROSOL

Those Ingredients listed above are subject to the reporting requirements of 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

Please call 1-800-527-9919 for additional information if you are a California customer. This MSDS is not intended for users in the state of California.

## Section XII - References

1. Threshold Limit Values for chemical substances and physical agents and biological exposure indices, ACGIH, 2007.
2. OSHA PEL.
3. Vendor's MSDS.
4. Registry of toxic effects of chemical substances, CCINFOWeb, 2007.
5. European Chemical Substances Information System (ESIS), International Uniform Chemical Information Database (IUCLID) Chemical Data Sheets.
6. ChemADVISOR, Inc. Database Release: 2007-4.

All the components of this product are in compliance with the Toxic Substances Control Act (TSCA) and are either listed on the TSCA inventory or otherwise exempted from listing.

-----  
IRR: Irritant, OSHA: Occupational Safety & Health Administration, IARC: International Agency for the Research on Cancer, TOX: Toxic, NFPA: National Fire Protection Association, ppm: Parts Per Million, UEL: Upper Explosion Limit, STEL: Short-term Exposure Limit, HMN: Human, mg/m3, IHL: Inhalation, COMB: Combustible, CORR: Corrosive, MUT: Mutagenic, CARC: Carcinogenic, N/A: Not Applicable, TLV: Threshold Limit Value, N/E: Not Established, ORL: Oral, FLAM: Flammable, ASPHYX: Asphyxiant, C.O.C.: Cleveland Open Cup, PNOR: Particles Not Otherwise Regulated, LEL: Lower Explosion Limit, mg/L: Milligrams per Liter, PNOT: Particles Not Otherwise Specified, g/L: Grams per Liter, PMCC: Pinsky-Martin Closed Cup, NTP: National Toxicology Program, µg/L: Micrograms per Liter, TCC: Tagliabue Closed Cup, SEV: Severe, RBT: Rabbit, INV: Intravenous, ACGIH: American Conference of Governmental Industrial Hygienists, PEL: Permissible Exposure Limit, MOD: Moderate, IPT: Intraperitoneal, gm/kg: Grams per Kilogram, C.C.C.: Cleveland Closed Cup, SKN: Skin, Milligrams per Cubic Meter, mg/kg: Milligrams per Kilogram, VOC: Volatile Organic Compound, SDT: Standard Draize Test, MSE: Mouse, GPG: Guinea Pig.

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE IN LIGHT OF CURRENT FORMULATION. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF.

CHEMSEARCH DIV. OF NCH CORP. assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage, or disposal of the product.

©2008 [NCH Corporation](#) All rights reserved.