

SAFETY DATA SHEET

Revision Date 21-Oct-2015 Version 2

1. IDENTIFICATION

Product identifier

Product Name SA9 BATTERY PROTECTOR & SEALER 5 OZ AE

Other means of identification

Product Code 80370 Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Battery Sealant

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address <u>Distributor</u>

ITW Permatex Canada
6875 Parkland Blvd. 35 Brownridge Road, Unit 1
Solon, OH 44139 USA Halton Hills, ON Canada L7G 0C6

Telephone: (800) 924-6994

Company Phone Number 1-87-Permatex

(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address mail@permatex.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Liquefied gas

Label elements

Emergency Overview

Danger

Causes skin irritation
Causes serious eye irritation
May cause drowsiness or dizziness
May be fatal if swallowed and enters airways
Extremely flammable aerosol

Contains gas under pressure; may explode if heated



Appearance Purple

Physical state Liquid Flammable Aerosol

Odor Solvent

Precautionary Statements - Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Wash face, hands and any exposed skin thoroughly after handling
Wear protective gloves/protective clothing/eye protection/face protection
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Do not spray on an open flame or other ignition source
Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

Precautionary Statements - Storage

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
ACETONE	67-64-1	15-35	*
XYLENE	1330-20-7	10 - 30	*
PROPANE	74-98-6	15-30	*
DISTILLATES (PETROLEUM), HYDROTREATED	64742-47-8	5-25	*
LIGHT			

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice Get medical advice/attention if you feel unwell.

Eve contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact IF ON SKIN:. Wash skin with soap and water. If skin irritation persists, call a physician.

Wash contaminated clothing before reuse.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED:. Call a physician or poison control center immediately. Do NOT induce

vomiting.

Self-protection of the first aiderUse personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

Extremely flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

Explosion data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin.

Use personal protective equipment as required.

Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. See Section 12 for additional

ecological Information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with

inert absorbent material. Sweep up and shovel into suitable containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing

vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

Contents under pressure. Do not puncture or incinerate cans.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Incompatible materials Strong oxidizing agents, Strong bases, Strong acids

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ACETONE	STEL: 750 ppm	STEL: 750 ppm TWA: 1000 ppm	
67-64-1	TWA: 500 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m ³
		(vacated) TWA: 1800 mg/m ³	-
		(vacated) STEL: 2400 mg/m ³ The	
		acetone STEL does not apply to the	
		cellulose acetate fiber industry. It is	
		in effect for all other sectors	
		(vacated) STEL: 1000 ppm	
XYLENE	STEL: 150 ppm	TWA: 100 ppm	-
1330-20-7	TWA: 100 ppm TWA: 435 mg/m ³		
		(vacated) TWA: 100 ppm	
		(vacated) TWA: 435 mg/m ³	
		(vacated) STEL: 150 ppm	
		(vacated) STEL: 655 mg/m ³	
PROPANE	TWA: 1000 ppm TWA: 1000 ppm		IDLH: 2100 ppm
74-98-6		TWA: 1800 mg/m ³	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1800 mg/m ³
		(vacated) TWA: 1800 mg/m ³	

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Gives a flame projection at full valve opening or flashback at any degree of valve opening

Butyl acetate = 1

Air = 1

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

Respiratory protectionUse NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid; Flammable Aerosol

Appearance Purple Odor Solvent

Odor threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

No information available

pH No information available
Melting point / freezing point
Boiling point / boiling range No information available
No information available

Flash point < -18 °C / < 0 °F

Evaporation rate > 1

Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
No information available
No information available
No information available

Vapor density >1 Relative density 0.85

Water solubility Insoluble in water Solubility in other solvents No information available Partition coefficient No information available No information available **Autoignition temperature Decomposition temperature** No information available Kinematic viscosity No information available **Dynamic viscosity** No information available **Explosive properties** No information available

Other Information

Oxidizing properties

Softening pointNo information availableMolecular weightNo information available

VOC Content (%) 45%

DensityNo information availableBulk densityNo information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions

Possibility of Hazardous Reactions

80370 - SA9 BATTERY PROTECTOR & SEALER 5 OZ AE

None under normal processing.

Conditions to avoid

Heat, flames and sparks. Temperatures >50 °C / 122 °F.

Incompatible materials

Strong oxidizing agents, Strong bases, Strong acids

Hazardous Decomposition Products

Carbon oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation May cause drowsiness or dizziness.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact May cause skin irritation and/or dermatitis.

Ingestion Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and

pneumonitis.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
ACETONE	= 5800 mg/kg (Rat)	-	= 50100 mg/m³ (Rat) 8 h
67-64-1			
XYLENE	= 3500 mg/kg (Rat)	> 1700 mg/kg (Rabbit) > 4350	= 29.08 mg/L (Rat) 4 h = 5000
1330-20-7		mg/kg (Rabbit)	ppm (Rat)4 h
PROPANE	=	=	= 658 mg/L (Rat) 4 h
74-98-6			
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat)4 h
64742-47-8			

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available. **Germ cell mutagenicity** No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
XYLENE	-	Group 3	-	-
1330-20-7		•		

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans Not classifiable as a human carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Target Organ Effects Central nervous system, Eyes, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 7132 mg/kg
ATEmix (dermal) 5971 mg/kg
ATEmix (inhalation-gas) 2432615 mg/l
ATEmix (inhalation-dust/mist) 7.5 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

15 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
ACETONE 67-64-1	-	4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 6210 - 8120: 96	10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 -
07 04 1		h Pimephales promelas mg/L LC50	12700: 48 h Daphnia magna mg/L
		static 8300: 96 h Lepomis	EC50
		macrochirus mg/L LC50	
XYLENE	-	13.4: 96 h Pimephales promelas	3.82: 48 h water flea mg/L EC50
1330-20-7		mg/L LC50 flow-through 2.661 -	0.6: 48 h Gammarus lacustris mg/L
		4.093: 96 h Oncorhynchus mykiss	LC50
		mg/L LC50 static 13.5 - 17.3: 96 h	
		Oncorhynchus mykiss mg/L LC50	
		13.1 - 16.5: 96 h Lepomis	
		macrochirus mg/L LC50	
		flow-through 19: 96 h Lepomis	
		macrochirus mg/L LC50 7.711 -	
		9.591: 96 h Lepomis macrochirus	
		mg/L LC50 static 23.53 - 29.97: 96	
		h Pimephales promelas mg/L LC50	
		static 780: 96 h Cyprinus carpio	
		mg/L LC50 semi-static 780: 96 h	
		Cyprinus carpio mg/L LC50 30.26 -	
		40.75: 96 h Poecilia reticulata mg/L	
		LC50 static	
DISTILLATES (PETROLEUM),	-	45: 96 h Pimephales promelas mg/L	4720: 96 h Den-dronereides
HYDROTREATED LIGHT		LC50 flow-through 2.2: 96 h	heteropoda mg/L LC50
64742-47-8		Lepomis macrochirus mg/L LC50	
		static 2.4: 96 h Oncorhynchus	
		mykiss mg/L LC50 static	

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition coefficient
ACETONE	-0.24
67-64-1	
XYLENE	2.77 - 3.15
1330-20-7	
PROPANE	2.3
74-98-6	

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastesThis material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

Contaminated packaging Do not reuse container.

US EPA Waste Number D001

80370 - SA9 BATTERY PROTECTOR & SEALER 5 OZ AE

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
ACETONE	-	Included in waste stream:	=	U002
67-64-1		F039		
XYLENE	-	Included in waste stream:	-	U239
1330-20-7		F039		

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
ACETONE	Ignitable
67-64-1	
XYLENE	Toxic
1330-20-7	Ignitable

14. TRANSPORT INFORMATION

DOT

UN/ID no 1950

Proper shipping name: Aerosols, Limited Quantity (LQ)

Hazard Class 2.1 Emergency Response Guide 126

Number

IATA

UN/ID no ID 8000

Proper shipping name: Consumer commodity

Hazard Class 9 ERG Code 9L

IMDG

UN/ID no 1950

Proper shipping name: Aerosols, Limited Quantity (LQ)

Hazard Class 2.1 EmS-No F-D, S-U

15. REGULATORY INFORMATION

International Inventories

TSCA Complies **DSL/NDSL** Complies **EINECS/ELINCS** Complies Complies **ENCS** Complies **IECSC KECL** Complies **PICCS** Complies AICS Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances **IECSC** - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

80370 - SA9 BATTERY PROTECTOR & SEALER 5 OZ AE

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
XYLENE - 1330-20-7	1.0
SARA 311/312 Hazard Categories	

Acute health hazard Yes
Chronic Health Hazard Yes
Fire hazard Yes
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE	100 lb	-	-	X
1330-20-7				

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemica	al Name H	azardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
ACET	ONE	5000 lb	-	RQ 5000 lb final RQ
67-6	64-1			RQ 2270 kg final RQ
XYLI	ENE	100 lb	-	RQ 100 lb final RQ
1330	-20-7			RQ 45.4 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ACETONE	X	X	X
67-64-1			
XYLENE	X	X	X
1330-20-7			
PROPANE	X	X	X
74-98-6			

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

A Compressed gases, B5 - Flammable aerosol, D2B - Toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 3 Instability 0

HMIS Health hazards 2 Flammability 3 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 21-Oct-2015

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the

date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet