

# Material Safety Data Sheet



Zep Inc.  
1310 Seaboard Industrial Blvd.  
Atlanta, GA 30318  
1-877-793-7776

## Section 1. Chemical Product and Company Identification

**Product name** VANDAL MARK REMOVER  
**Product use** Aerosol Cleaner  
**Product code** R062  
**Date of issue** 08/05/08 **Supersedes**

### Emergency Telephone Numbers

#### For MSDS Information:

Compliance Services 1-877-793-7776

#### For Medical Emergency

INFOTRAC: (877) 541-2016 Toll Free - All Calls Recorded

#### For Transportation Emergency

CHEMTREC: (800) 424-9300 - All Calls Recorded  
In the District of Columbia (202) 483-7616

#### Prepared By

Compliance Services  
1420 Seaboard Industrial Blvd.  
Atlanta, GA 30318

## Section 2. Hazards Identification

### Emergency overview

\*Hazard Determination System (HDS): Health, Flammability, Reactivity

**DANGER !**



FLAMMABLE. CAUSES EYE AND SKIN IRRITATION. HARMFUL IF ABSORBED THROUGH SKIN.

CONTENTS UNDER PRESSURE.

**NOTE: MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse effects are lessened by following all prescribed safety precautions, including the use of proper personal protective equipment.**

### Acute Effects

#### Routes of Entry

Dermal contact. Eye contact. Inhalation.

#### Eyes

Causes eye irritation. Inflammation of the eye is characterized by redness, watering and itching.

#### Skin

May cause skin irritation. May cause skin sensitization. May cause allergic reactions in certain individuals. Harmful if absorbed through the skin. Skin inflammation is characterized by itching, scaling, or reddening.

#### Inhalation

Avoid breathing vapors, spray or mists. Over-exposure by inhalation may cause respiratory irritation. Can cause central nervous system (CNS) depression.

#### Ingestion

Harmful if swallowed. Ingestion may cause nausea, weakness and central nervous system effects. Aspiration hazard if swallowed. Can enter lungs and cause damage.

### Chronic effects

Prolonged or repeated contact may dry skin and cause irritation. Repeated or prolonged contact with spray or mist may produce chronic eye irritation and severe skin irritation. Repeated or prolonged inhalation of vapors may lead to chronic respiratory irritation. Overexposure of this product by inhalation or absorption can produce central nervous system depression resulting in headache, nausea and/or dizziness. Contains material which may cause damage to the following organs: kidneys, liver, central nervous system (CNS).

**Additional Information: See Toxicological Information (Section 11)**

## Section 3. Composition/Information on Ingredients

ETHANOL; ethyl alcohol; grain alcohol	64-17-5	20 - 30
ISOPARAFFINIC SOLVENT; hydrotreated light distillate (petroleum)	64741-73-7	20 - 30
BENZYL ALCOHOL; alpha-hydroxytoluene; phenyl carbinol	100-51-6	20 - 30
D-LIMONENE; orange distillate; citrus terpene; cyclohexene, 1-methyl-4-(1-methylethenyl)-, (R)-	5989-27-5	5 - 15
HYDROCARBON PROPELLANT; blend of propane & isobutane	75-28-5; 74-98-6	5 - 15

**Section 4. First Aid Measures**

<b>Eye Contact</b>	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention immediately.
<b>Skin Contact</b>	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if irritation develops.
<b>Inhalation</b>	Move exposed person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. If affected person is conscious, give plenty of water to drink. Never give anything by mouth to an unconscious person. Get medical attention immediately.

**Section 5. Fire Fighting Measures**

National Fire Protection Association (U.S.A.)



<b>Flash Point</b>	Not available.
<b>Flammable Limits</b>	Not available.
<b>Flammability</b>	FLAMMABLE. (CSMA Method)
<b>Fire hazard</b>	Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.
<b>Fire-Fighting Procedures</b>	Use an extinguishing agent suitable for the surrounding fire. Fire-fighters should wear appropriate protective equipment. Cool closed containers exposed to fire with water. Do not release runoff from fire to sewers or waterways.

**Section 6. Accidental Release Measures**

**Spill Clean up** Large spills are unlikely due to packaging.

**Section 7. Handling and Storage**

<b>Handling</b>	Put on appropriate personal protective equipment (see section 8). Store and use away from heat, sparks, open flame or any other ignition source. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Watch for accumulation in low confined areas. Observe label precautions. Wash thoroughly after handling. Do not reuse container.
<b>Storage</b>	CONTENTS UNDER PRESSURE. Store in a cool, well-ventilated area away from incompatible materials and ignition sources. Do not puncture, incinerate or store the container at temperatures above 49°C (120°F) or in direct sunlight. Keep away from food, drink and animal feeding stuffs. Keep out of the reach of children.

**Section 8. Exposure Controls/Personal Protection****Product name**

ETHANOL; ethyl alcohol; grain alcohol

ISOPARAFFINIC SOLVENT; hydrotreated light distillate (petroleum)

HYDROCARBON PROPELLANT; blend of propane &amp; isobutane


**Exposure limits****ACGIH TLV / OSHA PEL (United States).**

TWA: 1000 ppm 8 hour(s).

**NIOSH REL (United States).**TWA: 1200 mg/m<sup>3</sup> Form: Vapor**ACGIH TLV / OSHA PEL (United States). Notes: Propane**

TWA: 1000 ppm 8 hour(s).

**Personal Protective Equipment (PPE)**

<b>Eyes</b>	Safety glasses.	
<b>Body</b>	Recommended: Viton gloves.	
<b>Respiratory</b>	Use with adequate ventilation. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Wear appropriate respirator when ventilation is inadequate.	

**Section 9. Physical and Chemical Properties**

<b>Physical State</b>	Liquid. [Aerosol.]	<b>Color</b>	Clear. Colorless.
<b>pH</b>	Not applicable	<b>Odor</b>	Citrus
<b>Boiling Point</b>	79.444°C (175°F)	<b>Vapor Pressure</b>	Not determined.
<b>Specific Gravity</b>	0.844	<b>Vapor Density</b>	Not determined.
<b>Solubility</b>	Insoluble in the following materials: cold water and hot water.	<b>Evaporation Rate</b>	Not determined.
		<b>VOC (Consumer)</b>	421 (g/l). 3.52 lbs/gal (50.0%)

**Section 10. Stability and Reactivity**

<b>Stability and Reactivity</b>	The product is stable.
<b>Incompatibility</b>	Keep away from heat, sparks and flame. Reactive or incompatible with the following materials: oxidizing materials.
<b>Hazardous Polymerization</b>	Will not occur.
<b>Hazardous Decomposition Products</b>	carbon oxides (CO, CO <sub>2</sub> )

**Section 11. Toxicological Information****Acute Toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Ethanol	LD50 Oral	Rat	7060 mg/kg	-
	LC50 Inhalation Vapor	Rat	20000 mg/m <sup>3</sup>	4 hours
Isoparaffinic Solvent; Hydrotreated light distillate (petroleum)	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
Benzyl alcohol	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Oral	Mouse	1580 mg/kg	-
	LD50 Oral	Rat	1230 mg/kg	-
	LD50 Oral	Rabbit	1040 mg/kg	-
	LC50 Inhalation Vapor	Rat	1000 ppm	8 hours

**Section 12. Ecological Information**

**Environmental Effects** No known significant effects or critical hazards.

**Aquatic Ecotoxicity**

Not available.

**Section 13. Disposal Considerations****Waste Information**

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.

**Waste Stream** Code: D001  
Classification: - [Hazardous waste]  
Origin: - [RCRA waste.]

**Section 14. Transport Information**

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label
<b>DOT Classification</b>	None.	Consumer commodity ORM-D			
<b>IMDG Class</b>	Not determined.				

NOTE: DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

PG\* : Packing group

**Section 15. Regulatory Information****U.S. Federal Regulations**

SARA 313 toxic chemical notification and release reporting:

No products were found.

**Clean Water Act (CWA) 307:** No products were found.

**Clean Water Act (CWA) 311:** No products were found.

**Clean Air Act (CAA) 112 regulated toxic substances:** No products were found.

All Components of this product are listed or exempt from listing on TSCA Inventory.

**State Regulations**

**California Prop 65** No products were found.

**Section 16. Other Information**

*To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.*

*Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.*

\*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.