

Swift Ind Arts

PARKS CORP -- LACQUER SANDING SEALER -- 8030-00N056896

=====  
Product Identification  
=====

Product ID:LACQUER SANDING SEALER

MSDS Date:04/01/1990

FSC:8030

NIIN:00N056896

MSDS Number: BWGTP

=== Responsible Party ===

Company Name:PARKS CORP

Box:5

City:SOMERSET

State:MA

ZIP:02726

Country:US

Info Phone Num:617-679-5938

Emergency Phone Num:617-679-5938

CAGE:G0179

=== Contractor Identification ===

Company Name:PARKS CORP

Address:MAIN ST

Box:5

City:SOMERSET

State:MA

ZIP:02726

Country:US

Phone:508-679-5938

CAGE:G0179

Company Name:PARKS CORPORATION

Box:5

City:SOMERSET

State:MA

ZIP:02726

Country:US

Phone:508-679-5938

CAGE:6L244

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NITROCELLULOSE; (COLLODION) (WET NITROCELLULOSE)

CAS:9004-70-0

RTECS #:QW0970000

Fraction by Wt: 10-38%

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:ISOPROPYL ALCOHOL (SARA 313)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 15-20%

OSHA PEL:400 PPM

ACGIH TLV:400 PPM; 500 STEL

Ingred Name:2-BUTANONE; (METHYL ETHYL KETONE) (MEK) (SARA 313) (CERCLA)

CAS:78-93-3

RTECS #:EL6475000  
Fraction by Wt: 2-10%  
OSHA PEL:200 PPM  
ACGIH TLV:200 PPM; 300 STEL  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:2-PENTANONE, 4-METHYL-; (METHYL ISOBUTYL KETONE) (HEXONE)  
(SARA 313) (CERCLA)

CAS:108-10-1  
RTECS #:SA9275000  
Fraction by Wt: 10-20%  
OSHA PEL:100 PPM  
ACGIH TLV:50 PPM; 75 STEL  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:LACOLENE; (LACTOL SPIRITS)  
CAS:64742-89-8  
Fraction by Wt: 10-20%  
OSHA PEL:N/K  
ACGIH TLV:N/K

Ingred Name:TOLUENE (SARA 313) (CERCLA)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 2-10%  
OSHA PEL:200 PPM  
ACGIH TLV:50 PPM, S  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE: INHALATION: TEMPORARY  
DIZZINESS, HEADACHE, POSSIBLY NAUSEA. SYMPTOMS DISAPPEAR WHEN  
EXPOSURE CEASES. EYE OR SKIN CONTACT: MAY CAUSE DISCOMFORT BY  
DEFATTING ACTION OF SOLVENT. CHRONIC: TOLUENE APPEARS ON NAVY  
LISTING OF OCCUPATIONAL CHEMICAL REPRODUCTIVE HAZARDS. SEEK  
CONSULTATION FROM (EFTS OF OVEREXP)  
Explanation of Carcinogenicity:NOT RELEVANT  
Effects of Overexposure:HLTH HAZ: APPROPRIATE HEALTH PROFESSIONALS  
CONCERNING LATEST HAZARD LIST INFORMATION AND SAFE HANDLING AND  
EXPOSURE INFORMATION . REPEATED CONTACT TO SKIN MAY CAUSE  
DERMATITIS. MAY CAUSE EYE IRRITATION.  
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====  
===== First Aid Measures =====

First Aid:INHAL: REMOVE PERSON TO FRESH AIR. IF OVERCOME BY VAPOR, CALL  
MD. IF BREATHING IS IRREGULAR OR STOPPED, START RESUSCITATION.  
ADMINISTER OXYGEN. INGEST: DO NOT INDUCE VOMITING. CALL MD. EYES:  
FLUSH WITH CLEAN WATER FOR AT LEAST 15 MINUTES. SKIN: WASH SKIN  
THOROUGHLY & REMOVE SATURATED CLOTHING. IF SYMPTOMS PERSIST, SEEK

## MEDICAL ATTENTION.

=====  
Fire Fighting Measures  
=====

Flash Point Method:TCC  
Flash Point:30.0F,-1.1C  
Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL, WATER SPRAY OR FOG.  
Fire Fighting Procedures:USE NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP  
WATER MAY BE UNSUITABLE AS EXTING MEDIA BUT HELPFUL IN KEEPING  
ADJACENT CNTNRS COOL. AVOID SPREADING (SUPDAT)  
Unusual Fire/Explosion Hazard:KEEP WORK AREAS FREE OF HOT METAL  
SURFACES AND OTHER SURFACES OF IGNITION.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE SOURCES OF IGNIT & PROVIDE VENT. LG  
SPILLS MAY BE SCOOPED UP W/NON-SPK TOOLS ON TO SAND, EARTH, CLAY,  
FLOOR ABSORBS & SHOVELED INTO CNTNRS FOR DISP. KEEP AWAY FROM  
SEWERS, STREAMS &/OR OTHER BODIES OF WATER. PROVIDE NIOSH/MSHA  
APPRVD (SUPDAT)  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE AWAY FROM HEAT, SPARKS AND OPEN  
FLAME. AVOID PROLONGED SKIN CONTACT. DO NOT BREATHE SPRAY MIST.  
Other Precautions:GROUND CNTNRS WHEN POURING & LIMIT FREE FALL TO FEW  
INCHES TO PREVENT STATIC SPKS. AVOID SPONT COMBUSTION OF CONTAMINATED  
RAGS/OTHER EASILY IGNITABLE ORG ACCUMULATIONS BY IMMEDIATE IMMERSION IN WATER.  
EMPTIED CNTNRS MAY RETAIN HAZARDOUS PROPERTIES. DO NOT CUT, (SUPDAT)

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:NIOSH/MSHA APPROVED MASK OR RESPIRATOR FOR  
ORGANIC VAPORS AS NECESSARY.  
Ventilation:ADEQUATE VENTILATION. LOCAL EXHAUST A MUST. MECHANICAL  
(GENERAL): EXPLOSION-PROOF.  
Protective Gloves:NEOPRENE RUBBER GLOVES.  
Eye Protection:ANSI APPROVED CHEM WORKERS GOGGLES .  
Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWERS SHOULD  
BE AVAILABLE. IMPERMEABLE APRON.  
Work Hygienic Practices:NO SMOKING.  
Supplemental Safety and Health  
FIRE FIGHT PROC: BURNING LIQUID W/WATER USED FOR COOLING PURPOSES.  
SPILL PROC: RESP PROT IF REQD. SMALL QUANTITIES MAY BE PICKED UP W/ABSORBING  
MATERIALS. OTHER PRECAUTIONS: PUNCTURE OR WELD ON OR NEAR CONTAINER. AVOID INHALATION  
OF VAPORS.

=====  
Physical/Chemical Properties  
=====

Boiling Pt:B.P. Text:180F,82C  
Vapor Pressure:71  
Vapor Density:HVR/AIR  
Spec Gravity:0.856 (H<sub>2</sub>O=1)  
Evaporation Rate & Reference:<1 N-BUTYL ACETATE  
Solubility in Water:NEGLIGIBLE

Appearance and Odor:LIGHT YELLOW, OPAQUE; LACQUER TYPE ODOR.  
Percent Volatiles by Volume:79

=====  
Stability and Reactivity Data  
=====

Stability Indicator/Materials to Avoid:YES  
AVOID CONTACT WITH STRONG OXIDIZING AGENTS.  
Stability Condition to Avoid:KEEP AWAY FROM SPARKS AND OPEN FLAME.  
Hazardous Decomposition Products:USUAL PRODUCTS OF COMBUSTION: CARBON  
MONOXIDE, CARBON DIOXIDE AND POSSIBLY ACROLEIN & OXIDES OF  
NITROGEN.

=====  
Disposal Considerations  
=====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND  
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.