



The Clorox Company
 1221 Broadway
 Oakland, CA 94612
 Tel. (510) 271-7000

Material Safety Data Sheet

I Product: CLOROX CLEAN-UP CLEANER WITH BLEACH - SPRAY FORMULA

Description: CLEAR, FAINT YELLOW LIQUID WITH CHARACTERISTIC BLEACH ODOR

Other Designations	Distributor	Emergency Telephone Nos.
Clorox Clean-Up Clean-Up dilutable Clorox Clean-Up Cleaner with Bleach	Clorox Sales Company 1221 Broadway Oakland, CA 94612	For Medical Emergencies call: (800) 446-1014 For Transportation Emergencies Chemtrac (800) 424-9300

II Health Hazard Data	III Hazardous Ingredients									
<p>Moderate eye irritant. Mild to moderate skin irritant. Occasional clinical reports suggest a low potential for skin sensitization upon exaggerated exposure to sodium hypochlorite if skin damage (e.g., irritation) occurs during exposure. Routine clinical tests conducted on intact skin with this product found no sensitization in the test subjects. Exposure to vapor or mist may irritate eyes, nose, throat, lungs. Harmful if swallowed. May cause nausea and vomiting if swallowed. The following medical conditions may be aggravated by exposure to high concentrations of vapor or mist: heart conditions or chronic respiratory problems such as asthma, emphysema, chronic bronchitis or obstructive lung disease. Under normal consumer-use conditions, the likelihood of any adverse health effects is low.</p> <p>FIRST AID:</p> <p>EYE CONTACT: Remove any contact lenses, and flush eyes thoroughly with water for 15 minutes. If irritation persists, call a physician.</p> <p>SKIN CONTACT: Remove contaminated clothing; wash affected skin with water.</p> <p>IF BREATHING IS AFFECTED: Get fresh air immediately.</p> <p>IF SWALLOWED: Drink a glass of water. Call a physician.</p>	<table border="1"> <thead> <tr> <th>Ingredient</th> <th>Concentration</th> <th>Worker Exposure Limit</th> </tr> </thead> <tbody> <tr> <td>Sodium hypochlorite CAS #7681-52-9</td> <td>1-5%</td> <td>none established</td> </tr> <tr> <td>Sodium hydroxide CAS #1310-73-2</td> <td>0.5-2%</td> <td>2 mg/m³, Ceiling-TLV 2 mg/m³, Ceiling-Federal OSHA PEL</td> </tr> </tbody> </table> <p>TLV = Threshold Limit Value Source: ACGIH 1992-1993 PEL = Permissible Exposure Limit Source: OSHA</p> <p>None of the ingredients in this product are on the IARC, OSHA or NTP carcinogen lists.</p>	Ingredient	Concentration	Worker Exposure Limit	Sodium hypochlorite CAS #7681-52-9	1-5%	none established	Sodium hydroxide CAS #1310-73-2	0.5-2%	2 mg/m ³ , Ceiling-TLV 2 mg/m ³ , Ceiling-Federal OSHA PEL
Ingredient	Concentration	Worker Exposure Limit								
Sodium hypochlorite CAS #7681-52-9	1-5%	none established								
Sodium hydroxide CAS #1310-73-2	0.5-2%	2 mg/m ³ , Ceiling-TLV 2 mg/m ³ , Ceiling-Federal OSHA PEL								

IV Special Protection and Precautions	V Transportation and Regulatory Data
<p>Hygienic Practices: Do not get in eyes or on clothing. Avoid prolonged or repeated skin contact. Avoid prolonged breathing of vapor. Use only in well-ventilated areas.</p> <p>Personal Protection: Wear safety glasses. For sensitive skin or repeated/prolonged use, wear gloves.</p> <p>Ventilation: Use general ventilation to minimize exposure to gases or aerosols associated with this product.</p>	<p>U.S. DOT Hazard Class: Not restricted</p> <p>U.S. DOT Proper Shipping Name: compound cleaning liquid</p> <p>EPA CERCLA/SARA TITLE III: This product contains no chemicals regulated under Section 313 and contains sodium hydroxide (CAS# 1310-73-2, <1%) which is regulated under Section 304/CERCLA. Packaged product may be regulated under Sections 311/312 of SARA Title III.</p> <p>TSCA - All chemicals in this product are listed on the TSCA Inventory</p>

VI Spill Procedures/Waste Disposal	VII Reactivity Data
<p>Spill Procedures: Absorb and containerize. Wash down residual to sanitary sewer. Contact the sanitary treatment facility in advance to assure ability to process washed-down material.</p> <p>Waste Disposal: Dispose of in accordance with all applicable federal, state, and local regulations.</p>	<p>Stable under normal use and storage conditions. Strong oxidizing agent. Reacts with other household chemicals such as toilet bowl cleaners, rust removers, acids or ammonia-containing products to produce hazardous gases, such as chlorine and other chlorinated compounds. Prolonged contact with metal or old porcelain may cause pitting or discoloration.</p>

VIII Fire and Explosion Data	IX Physical Data
<p>Flashpoint: greater than 200°F</p> <p>Fire Extinguishing Agents: Water spray, dry chemical or carbon dioxide (CO₂).</p> <p>Special Fire-Fighting Procedures: None</p> <p>Unusual Fire and Explosion Hazards: None</p>	<p>Appearance: Clear, faint yellow liquid</p> <p>Odor: Characteristic bleach odor</p> <p>pH: 12.4 - 12.8</p> <p>Solubility in water: Completely soluble</p> <p>Specific gravity (water = 1): 1.034 at 25 °C</p>