Page 1

# MATERIAL SAFETY DATA SHEET MSDS

MSDS875

ITEM NUMBER: 875 -

VERSION 3 EFFECTIVE DATE: 4/12/01 SUPERCEDES DATE: 6/05/00 PREPARED BY: Ron Cepa

Section(s) Revised: II, IV, VI, VIII

IDENTITY (As Used On Label and List): DUST MOP TREATMENT

EMERGENCY MEDICAL Telephone# 1-866-836-8855 (24 HRS)

Outside the U.S.A. Call 952-852-4646

PRODUCT HAZARD RATINGS (HMIS): - Health = 2, Fire = 4, Reactivity = 0, Protective Equipment = A

(Rating Legend: 4 = Extreme, 3 = Serious, 2 = Moderate, 1 = Slight, 0 = Minimal)

#### **SECTION I**

CLAIRE MANUFACTURING TELEPHONE NUMBER FOR INFORMATION: 1-800-252-4731

500 VISTA AVE. DATE PRINTED: August 8, 2005

ADDISON, IL 60101 NAME OF PREPARER: Regulatory Compliance

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION					
Chemical Names	CAS#	SARA Title III SEC 313	ACGIH TLV/TWA-STEL	OSHA PEL/TWA-STE	% By Wt.
Mineral spirits	64742-48-9	No	177ppm*	177ppm*	5-10
Isoparaffinic Solvent	64742-47-8	No	NE	300ppm	60-70
Propane	68476-85-7	No	1000ppm	NE	10-20

<sup>\*</sup> ExxonMobil recommendation

Balance of ingredients are non-hazardous or below reportable levels.

# **SECTION III - PHYSICAL CHARACTERISTICS**

Boiling Point: NA Vapor Pressure (psig): 115@130F Specific Gravity (H20=1): <1
Solubility/Water: Negligible Vapor Density (AIR=1): >1 Evaporation Rate (Ether=1): <1

Appearance and Odor: Misty spray/colorless liquid

#### SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Aerosol Flammability: Product is to be labeled as extremely flammable as described in 16 CFR 1500.3 and 1500.45.

Flashpoint: <0F (Propellant); >120F (Concentrate)

Flammable Limits - % Volume In Air (Propellant): LEL: 2.2 UEL: 9.5

Extinguishing Media: Carbon dioxide, foam and/or dry chemical may be used.

Special Fire Fighting Procedures: Containers should be cooled with water to prevent vapor pressure build up.

Use equipment or shielding, as required, to protect personnel from bursting, rupturing or venting containers.

Unusual Fire and Explosion Hazards: At elevated temperatures (over 54C-130F) containers exposed to direct flame or heat contact should be cooled with water to prevent weakening of container structure.

# **SECTION V - REACTIVITY DATA**

Stability: Stable Hazardous Polymerization: NA

Incompatibility (Materials to Avoid): Avoid heat, flame and oxidizing agents

Hazardous Decomposition Products: Carbon dioxide, carbon monoxide and additional toxic chemicals may be formed in small amounts.

Conditions to Avoid: Do not store above 54C-130F. Keep away from heat, direct sunlight, open flames or sparks. Dropping of containers may cause bursting.

#### SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry - Inhalation: X Eyes: X Skin: X Ingestion:

Signs and Symptoms of Exposure: Inhalation may cause dizziness and drowsiness. Eye contact may be irritating. Skin contact may cause redness or irritation. Ingestion of aerosols is not a likely route however; ingestion of the liquid may result in vomiting which could cause aspiration pneumonitis.

Medical Conditions Generally Aggravated by Exposure: Preexisting skin or eye disorders may be aggravated by exposure to this product.

Emergency and First Aid Procedures: Eye Contact: Flush eyes with plenty of water for 15 minutes while holding eyelids open. Get medical attention if irritation persists. Skin Contact: Remove contaminated clothing.

MSDS875

Flush skin with water; follow by washing with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned. Inhalation: Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention. Ingestion: Get medical attention. NOTE TO PHYSICIAN: Product contains approximately 80% petroleum distillate. If more than 2.0ml per kg has been ingested and vomiting has not occurred, emesis should be induced with supervision. If symptoms such as loss of gag reflex, convulsions or unconsciousness occur before emesis, gastric lavage using a cuffed endotracheal tube should be considered.

CARCINOGENICITY: No regulated ingredients.

**TOXICITY INFORMATION:** 

No data available.

# SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Releases or Spilled: Remove all sources of ignition and ventilate area. Soak up spill with an inert absorbent and place into a designated disposal container. Consult local regulatory agency for proper disposition of material.

Waste Disposal Method: Do not puncture or incinerate containers. When contents are depleted continue to depress button until all gas is expelled. Dispose of container in accordance with local, state, and federal regulations.

Handling And Storing: Avoid breathing vapor. Keep away from heat and flame. Use with adequate ventilation. Do not puncture or incinerate containers. Do not expose to direct sunlight or store at temperatures above 130F (54C). Store as Level 3 Aerosol (NFPA 30B).

Other Precautions: Please read and follow the directions on the product label; they are your best guide to using this product in the most effective way, and give the necessary safety precautions to protect your health.

# **SECTION VIII - EMPLOYEE PROTECTION**

Respiratory Protection (Type): None required if good ventilation is maintained. If exposure exceeds occupational exposure limits (Sec. II), use a NIOSH approved respirator to prevent overexposure.

Ventilation: General ventilation is adequate under normal conditions, mechanical ventilation is optional.

Protective Gloves: Chemical resistant gloves are recommended - consult glove manufacturer to determine the proper type for a specific operation.

Eye Protection: Chemical safety glasses are recommended.

Other Protective Clothing or Equipment: Wear impervious clothing to prevent skin contact.

Work/Hygienic Practices: Ensure strict sanitary conditions are conformed to when working around chemicals.

Protective clothing and equipment should be in accordance with 29 CFR 1910.132 and CFR 1910.133.

# **SECTION IX - OTHER REGULATORY CONTROLS**

Governmental Listings: Ingredients of this product are listed on the EPA/TSCA Inventory of Chemical Substances.

# SECTION X - TRANSPORTATION REQUIREMENTS (D.O.T. CLASSIFICATION)

Shipping Name: Consumer Commodity

Hazard Class: ORM-D

NG-- Negligible NA-- Not Applicable NE-- Not Established UN-- Unavailable ND-- Not Determined While the information set forth herein is believed to be accurate as of the date hereof, the Company makes no warranty or guarantee, express or implied, and disclaims all liability arising out of the use of this information.

EFFECTIVE DATE: 4/12/01 SUPERCEDES DATE: 6/05/00 PREPARED BY: Ron Cepa