



MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT IDENTIFICATION

Product:Goof Off®Manufacturer:Valspar CorporationAddress:411 North Darling, Fremont MI 49412

Code No.: NA Telephone: (231 SP Code: DA8

NA : (231) 924-3950 DA8050

SECTION 2 - PRODUCT COMPONENTS

	Component Name	<u>OSHA</u>	<u>ACGIH TLV</u>	<u>Wt. %</u>	<u>CAS Number</u>
		PEL			
1)	*Xylene	100 ppm	100 ppm	80-85	1330-20-7
2)	*Ethyl Benzene	100 ppm	100 ppm	10-15	100-41-4
3)	*Diethylene glycol monomethyl ether	30 ppm ¹	30 ppm ¹	<5	111-77-3
4)	Nonionic surfactant	NE	NE	<2	9016-45-9

*SARA III SECTION 313 TOXIC CHEMICAL

SECTION 3 - PHYSICAL AND CHEMICAL CHARACTERISTICS

Boiling Point:	147°F IBP	Specific Gravity:	0.865 typical
Vapor Pressure:	7 ²	Water Soluble:	No
Vapor Density (Air = 1):	>1	Water Reactive:	No
Volume % Volatile:	100	pH:	NA
Appearance and Odor:	Clear liquid, sol	vent odor.	

SECTION 4 - FIRE AND EXPLOSION INFORMATION

Flash Point (Method):				
Flammable Limits, LEL:	0.9 ²	UEL:	ND	
Extinguishing Media:	Extinguishing Media: Foam, dry chemical, carbon dioxide			
Special Fire-fighting Proc	pecial Fire-fighting Procedures: Use SCBA. Water is not suitable as an extinguishi			
/ Jnusual Fire and Explosion Hazards:		media, but may be used to cool Pressure may develop in closed overheated.	-	

SECTION 5 - REACTIVITY DATA

Stable:YesConditions to Avoid:Heat, sparks, open flame.Incompatibility:Strong oxidizers like chlorine or concentrated oxygen.Hazardous Decomposition Products:Combustion may produce smoke, carbon monoxide,
other undetermined oxides and fumes.Polymerization:NoConditions to Avoid:None known

SECTION 6 - HEALTH HAZARDS

Primary Routes of Entry: Oral:

Yes Carcinogenic Listing: NTP: No

GOFF OFF® MATERIAL SAFETY DATA SHEET, CONTINUED

	Inhalation: Skin Absorb.:	Yes Ves		IARC: ACGIH:	No No
HMIS Rating: Healt		mmability: 3	Reactivity:	0	110
Signs/Symptoms of Exp			tion. Vapor or m	-	on
5 7	-		ea, CNS depress		
	may cause	gastrointestinal	distress	-	
Emergency First Aid Pro	ocedures				
Eye Contact:	Flush with running		utes, holding lid d	open to exp	ose
	eye surface. Conta				
Skin Contact:	Remove contamina			ith mild soa	ap and
	water. Contact phy		•		
Inhalation:	Remove to fresh a		artificial respirati	ion if neces	ssary.
	Contact physician i	-			
Ingestion:	CONTACT PHYSI	CIAN OR POISC	N CONTROL CI	ENTER	
	IMMEDIATELY.				
Chronic Hazards:	Health studies hav				
	risks that may vary	• •		•	
	occupational overe			4	
	brain and nervous concentration and				erate
	precaution, exposu	-			
			apora anoulu ne l		

SECTION 7 - SPECIAL PRECAUTIONS/SPILL & LEAK PROCEDURES

Precautions for Storage and Handling:	Keep containers closed when not in use. Do not
Other Precautions:	use or store near open flame or strong oxidizers. Avoid breathing vapors or mists; prolonged or repeated skin contact.
Spill or Leak Precautions:	Remove ignition sources. Dike and take up with absorbent material. Ensure adequate ventilation.
Waste Disposal Method:	Comply with all applicable regulations.

SECTION 8 - SPECIAL PROTECTION & PRECAUTIONS

Respiratory Protection:	None required in normal use but an effective NIOSH/MSHA approved respirator should be used at any time when vapor concentrations exceed established standards.			
Ventilation Type Required:	Adequate to maintain level below established standards.			
Local Exhaust:	Yes Rate: >60 fpm Mech. (General) No			
Gloves: Chemical resistant				
Eye Protection: Face shield or safety glasses recommended.				
Other Clothing/Equipment: None required in normal use.				
Work/Hygienic Practices:	Basic good housekeeping. Wash hands before eating or smoking. Smoke only in designated areas.			

SECTION 9 - SHIPPING/LABELING INFORMATION

DOT ID Number:

GOFF OFF® MATERIAL SAFETY DATA SHEET, CONTINUED

DOT Hazard Class: DOT Proper Shipping Name: DOT Precautionary Label: Packing Group: IMO/IATA ID Number: IMO/IATA Hazard Class: IMO Proper Shipping Name: IATA Proper Shipping Name: IMO/IATA Precautionary Label: IMO/IATA Precautionary Label: IMO/IATA Packing Group: IMO Page Number: Marine Pollutant:	3 ³ Xylene solution ³ Flammable Liquid diamond ³ II ³ UN1307 / UN1307 3 / 3.2 Xylene solution Xylene solution Flammable Liquid diamond / Flammable Liquid diamond II / II 3292 No
--	--

In Case of Transportation Emergency, Call Chemtrec 1-800-424-9300

¹ Manufacturer's recommendation

•7

² Value based on component data

³49CFR §173.150 (Consumer Commodity) may be applicable for certain size containers in domestic ground transportation.

A	bbreviations		
NA	Not Applicable	mppcf	Million Parts per Cubic Foot
N AV	Not Available	ppm	Parts per Million
ND	Not Determined	mg/m ³	Milligrams per Cubic Meter
NE	None Established	CĀS	Chemical Abstract Service
NTP	National Toxicology Program	SCBA	Self Contained Breathing Apparatus
IBP	Initial Boiling Point	fpm	Feet per Minute, Face Velocity
тсс	Tagliabue Closed Cup	•	• • •
COC	Cleveland Open Cup		
IARC	International Agency for Research on Cancer		
OCUA	Occupational Sofaty and Health Administration		

OSHA Occupational Safety and Health Administration

ACGIH American Conference of Governmental Hygienists

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.

Valspar Corporation Fremont, MI USA

(

Prepared by: Date: Revision: Steve Eckert 7-18-02 C-7

(

"range of the second