

Material Safety Data Sheet

Section 1: Product & Company Identification

Product Name:

Dry Moly Lube

Product Number (s):

03084, 83084

Manufactured By:

CRC Industries, Inc. 885 Louis Drive Warminster, PA 18974

www.crcindustries.com

General Information Technical Assistance (215) 674-4300

(800) 521-3168

Customer Service

(800) 272-4620

24-Hr Emergency (CHEMTREC)

(800) 424-9300

Section 2: Hazards Identification

Emergency Overview

Appearance & Odor: Dark viscous liquid, solvent odor

DANGER

Extremely Flammable. Harmful or Fatal if Swallowed. Eye and Skin Irritant. Contents Under Pressure

As defined by OSHA's Hazard Communication Standard, this product is hazardous.

Potential Health Effects:

EYE:

May cause eye irritation, including redness, itching or burning sensation.

SKIN:

Prolonged or repeated exposure may cause irritation. Symptoms of overexposure

include redness, itching and burning of skin.

INHALATION:

May cause irritation of the upper respiratory system or nervous system depression (headache, dizziness, nausea, and loss of coordination). Extreme overexposure

may result in unconsciousness and possibly death.

INGESTION:

Ingestion of aerosol product is not expected during normal use.

CHRONIC EFFECTS:

Prolonged overexposure may cause adverse effects to the liver and urinary

systems.

TARGET ORGANS:

liver and urinary systems

Medical Conditions Aggravated by Exposure:

Unknown

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Product Name: Dry Moly Lube

Section 3: Composition/Information on Ingredients

| COMPONENT | CAS NUMBER | % by Wt. | |
|----------------------|------------|----------|--|
| Propane | 74-98-6 | 5 - 15 | |
| Butane | 106-97-8 | 15 - 25 | |
| Heptane | 142-82-5 | 3 - 8 | |
| Mineral Spirits | 64742-88-7 | 1 - 5 | |
| 2-Propanol | 67-63-0 | 20 - 30 | |
| Acetone | 67-64-1 | 30 - 40 | |
| Molybdenum Disulfide | 1317-33-5 | 1 - 5 | |

Section 4: First Aid Measures

Eye Contact:

Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

Skin Contact:

Remove contaminated clothing and wash affected area with soap and water. Call a physician

if irritation persists. Wash contaminated clothing prior to re-use.

Inhalation:

Remove person to fresh air. Keep person warm and quiet. If not breathing, give artificial

respiration. If breathing is difficult give oxygen. Call a physician.

Ingestion:

Do not induce vomiting. Get medical attention immediately.

Note to Physicians:

Treat symptomatically.

Section 5: Fire-Fighting Measures

Flammable Properties:

This product is extremely flammable in accordance with aerosol flammability

definitions (16 CFR 1500.3(c)(6)).

Flash Point:

< 0°F

Upper Explosive Limit:

ND

Autoignition Temperature:

ND

Lower Explosive Limit:

ND

Suitable Extinguishing Media:

Carbon dioxide, dry chemical, foam

Products of Combustion:

Carbon dioxide and carbon monoxide

Protection of Fire-Fighters:

Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye

and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product

decomposition.

Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush

into sewers or storm drains.

Methods for Containment & Clean-up: Remove all sources of ignition. Dike area to contain spill. Ventilate the area

with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used

absorbents into proper waste containers.

Section 7: Handling and Storage

Handling Procedures: Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may

ignite explosively. During use and until all vapors are gone: Keep area ventilated. Do not smoke. Extinguish all flames, pilot lights, and heaters. Turn off stoves, electric tools and

other appliances, and any other source of ignition.

Storage Procedures: Store in a cool dry area out of direct sunlight. Aerosol cans must be maintained below 120 F

to prevent cans from rupturing. Store out of reach of children.

Aerosol Storage Level: III

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

| | OSHA | | ACGIH | | OTHER | | |
|-----------------------|------|-------------|---------|--------|-----------|--------|-------------------|
| COMPONENT | TWA | STEL | TWA | STEL | TWA | SOURCE | UNIT |
| Propane | 1000 | NE | 1000 | NE | NE | | ppm |
| Butane | 800 | NE | 1000 | NE | NE | | ppm |
| Heptane | 500 | NE | 400 | 500 | NE | | ppm |
| Mineral Spirits | NE | NE | NE | NE | NE | | |
| 2-Propanol | 400 | NE | 200 | 400 | NE | | ppm |
| Acetone | 1000 | NE | 500 | 750 | NE | | ppm |
| Molybdenum Disulfide | NE | NE | 10 | NE | NE | | mg/m ³ |
| N.E. – Not Establishe | d | (c) – ceili | ng (s)- | – skin | (v) – vac | ated | |

Engineering Controls:

Area should have ventilation to provide fresh air. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations.

Respiratory Protection:

None required for normal work where adequate ventilation is provided. If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies.

Product Number (s): 03084, 83084

Product Name: Dry Moly Lube

Eye/face Protection:

For normal conditions, wear safety glasses. Where there is reasonable probability of liquid

contact, wear splash-proof goggles.

Skin Protection:

Use protective gloves such as nitrile or neoprene. Also, use full protective clothing if there

is prolonged or repeated contact of liquid with skin.

Section 9: Physical and Chemical Properties

Physical State: liquid
Color: charcoal color
Odor: solvent odor
Specific Gravity: 0.71
Initial Boiling Point: ND
Freezing Point: ND

Vapor Pressure: ND

Vapor Density: > 1 Evaporation Rate: > 1 (air = 1) (ether = 1)

Solubility: NA pH: NA

pH: NA Volatile Organic Compounds:

wt %: 61.8

g/L: 438.78

lbs./gal: 3.66

Section 10: Stability and Reactivity

Stability:

Stable

Conditions to Avoid:

Sources of ignition; temperature extremes

Incompatible Materials:

None known

Hazardous Decomposition Products:

Carbon dioxide and carbon monoxide

Possibility of Hazardous Reactions:

No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

ACUTE EFFECTS

| Component | Test | Result | Route | Species |
|------------|------|---------------|------------|----------------|
| 2-Propanol | LD50 | 12,800 mg/kg | Dermal | Rabbit |
| 2-Propanol | LC50 | 16,000 ppm/8H | Inhalation | Rat |
| Acetone | LD50 | 5800 mg/kg | Oral | Rat |

CHRONIC EFFECTS

Carcinogenicity:

Component

Result

OSHA: IARC: None listed None listed

NTP:

None listed

Product Name: Dry Moly Lube

Mutagenicity:

Unknown

Other:

None

Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity:

Acetone - 48H LC50 Daphnia: 10 mg/l

Persistence / Degradability:

No information available No information available

Bioaccumulation / Accumulation: Mobility in Environment:

No information available

Section 13: Disposal Considerations

Disposal:

The dispensed liquid product is a RCRA hazardous waste for the characteristic of ignitability with a waste

code of D001. (See 40 CFR Part 261.20 - 261.33).

Aerosol containers should be fully emptied and depressurized before disposal. Empty containers may be

recycled.

All disposal activities must comply with federal, state and local regulations. Local regulations may be more stringent than state or national requirements.

Section 14: Transport Information

Proper shipping description:

US DOT (ground):

Consumer Commodity, ORM-D

Special Provisions:

None

Section 15: Regulatory Information

U.S. Federal

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients:

Acetone (5,000 lbs)

Product Number (s): 03084, 83084

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS):

None

Section 311/312 Hazard Categories:

Fire Hazard

Yes

Reactive Hazard

No

Release of Pressure

Yes

Product Number (s): 03084, 83084 Product Name: Dry Moly Lube

Acute Health Hazard

Yes No

Chronic Health Hazard

Section 313 Toxic Chemicals:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and

Reauthorization Act of 1986 and 40 CFR Part 372:

None

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs):

None

State Regulations

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm:

toluene (0.165%), benzene &

acetaldehyde (trace)

State Right to Know:

New Jersey:

74-98-6, 106-97-8, 142-82-5, 67-63-0, 67-64-1, 1317-33-5

Pennsylvania:

74-98-6, 106-97-8, 142-82-5, 67-63-0, 67-64-1

Massachusetts:

74-98-6, 106-97-8, 142-82-5, 67-63-0, 67-64-1

Rhode Island:

74-98-6, 106-97-8, 142-82-5, 67-63-0, 67-64-1

Additional Regulatory Information:

None

Section 16: Other Information

NFPA: HMIS:

Health: 2

Flammability:

Reactivity:

Health: 2 Flammability:

Reactivity:

PPE: В

Prepared By:

Michelle Rudnick

CRC #:

03084

Revision Date:

01/03/2008

Changes since last revision:

MSDS reformatted in accordance with ANSI Z400.1-2004

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

CAS:

Chemical Abstract Service

NA:

Not Applicable

ppm:

Parts per Million

ND: NE:

Not Determined Not Established

TCC: PMCC:

Tag Closed Cup Pensky-Martens Closed Cup Personal Protection Equipment

g/L: lbs./gal: grams per Liter pounds per gallon

PPE: TWA:

Time Weighted Average

STEL:

Short Term Exposure Limit

OSHA:

Occupational Safety and Health Administration

ACGIH

American Conference of Governmental Industrial Hygienists

NIOSH

National Institute of Occupational Safety & Health