



MATERIAL SAFETY DATA SHEET

SECTION 1 – IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: BREAKAWAY

Manufacturer's Product Code: 5064

Other Names: High temperature anti-seize compound.

Major Recommended Uses: As an aerosol anti-seize compound and light lubricant for nuts, bolts and other industrial applications.

Supplier's Details: Mantek
7 Ralph Street, Alexandria
Sydney NSW 2015
Telephone Number (Office Hours): (02) 9669 0261
Fax Number: (02) 9693 1562
Emergency Telephone Number: (02) 9214 0755

Date of Issue: May 2004

SECTION 2 – HAZARDS IDENTIFICATION

Hazard Classification: NOT classified as hazardous according to the criteria of NOHSC.

Dangerous Goods Class & Sub-risk: Class 2, no sub-risk.

Poisons Schedule: None allocated.

Risk Phrases: Flammable.

Safety Phrases: Keep out of reach of children
Avoid contact with skin and eyes, and avoid breathing spray mist.
Use in well-ventilated area.

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients

Chemical Entity	CAS No	Proportion	Synonyms
'INGREDIENTS DETERMINED NOT TO BE HAZARDOUS'			
		to 100%	

SECTION 4 – FIRST AID MEASURES

Skin: Wash affected areas with plenty of soap and water for several minutes. Seek medical attention if irritation develops.

Eye: Rinse eyes with water for several minutes. Seek medical attention if irritation develops.

Inhalation: Remove to fresh air. Seek medical attention if respiratory irritation develops or if breathing becomes difficult.

Ingestion: Give 3-4 glasses of water, but do NOT induce vomiting. If vomiting occurs, give fluids again. Seek medical attention if discomfort occurs.

First Aid Facilities: General eyewash.

Advice to Doctor: There is no specific antidote. Treat the patient symptomatically.

Additional Information: Medical conditions aggravated by exposure are pre-existing respiratory and skin conditions such as asthma, emphysema and dermatitis. Target organs: Central nervous system, lungs, kidneys and spleen. The primary route of entry into the body is via inhalation.

SECTION 5 – FIRE FIGHTING MEASURES

Suitable Extinguishing Media: In the event of a fire, powder, foam and CO2 are the recommended extinguishing agents.

Special Protective Equipment and Precautions for Fire Fighters: Fire fighters should wear self-contained breathing apparatus and full protective gear.

Fire/Explosive Hazards: Product may react with acids, bases or steam to produce flammable hydrogen gas. Flame extension is >45cm; burnback is 7-10cm.

Hazchem Code: 2Y

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Wear appropriate protective clothing.

Methods and Materials for Containment and Clean Up: Due to the nature of aerosol packaging, a large spill is unlikely. For a small spill, ventilate the area and absorb with an inert material. Dispose of waste in a closed, labelled container in accordance with local, state and Commonwealth laws. Typical disposal is to wrap the empty aerosol container in several layers of newspaper and dispose of in the garbage. Do not puncture or incinerate the can.

SECTION 7 – HANDLING AND STORAGE

Precautions for Safe Handling: Observe precautions stated on product label, and follow industry safety regulations. Eating and smoking should be prohibited where the preparation is used. Use with caution around heat, sparks, pilot lights, static electricity and open flame.

Conditions for Safe Storage: Store indoors in the in original container. Store in a dry, well-ventilated area. Store below 49°C.

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Standards: Not established for this mixture. The exposure limits for individual components follow:

Mineral oil:	TLV TWA - 5mg/m ³
Aluminium:	TLV TWA - 10mg/m ³
White Spirits:	TLV TWA – 100ppm; 790mg/m ³
Talc:	TLV TWA – 2.5mg/m ³
Propane/butane propellant:	TLV TWA – 800ppm; 1900mg/m ³

Engineering Controls: General exhaust is usually adequate, although local ventilation is recommended to control exposure from operations that can generate mists or vapours.

Personal Protective Equipment:

Eye/Face Protection: Wear safety glasses if the method of use presents the likelihood of eye contact. AS1336 and AS/NZS1337 should be consulted for information on eye protection.

Skin Protection: Neoprene or nitrile rubber gloves should be worn if repeated or prolonged skin contact is likely.

Respiratory Protection: None required under normal conditions of use. If misting is likely to occur, or if used in poorly ventilated areas where exposure will be above the TLV, an approved organic vapour respirator meeting the requirements outlined in AS/NZS 1715 and AS/NZS 1716 should be used.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Opaque, grey, viscous liquid with alcohol odour.
pH:	Not applicable
Vapour Pressure:	40-60 PSI
Vapour Density:	1.1 (Air = 1)
Boiling Point:	>288°C
Melting Point:	Not applicable
Solubility in Water (g/L):	Negligible
Specific Gravity:	1.06 (Water = 1)
Flashpoint:	149°C
Flashpoint Method:	Cleveland Open Cup
Flammability Limits:	LEL: 0.6; UEL: 8.0
% Volatiles by Volume:	92.9%
Evaporation Rate:	0.05 (BU A/C = 1)

SECTION 10 – STABILITY AND REACTIVITY

Stability: Stable.

Hazardous Polymerisation: Will not occur.

Conditions/Materials to Avoid: Avoid strong oxidising agents such as chlorine bleach and concentrated hydrogen peroxide; reducing agents such as sodium thiosulphate; strong acids and bases; and halogenated hydrocarbons.

Hazardous Decomposition Products: Oxides of carbon and aluminium oxide.

SECTION 11 – TOXICOLOGICAL INFORMATION

Health Effects:

Acute - Swallowed: May cause irritation with possible nausea, vomiting and diarrhoea.

Acute - Eye: May cause irritation seen as tearing and redness.

Acute - Skin: May cause irritation seen as itching and redness.

Acute - Inhaled: May cause respiratory irritation seen as coughing and sneezing. Inhalation of large amounts may cause dizziness, headache and other central nervous system effects.

Chronic: Due to the use pattern of this product, the likelihood of any chronic effects occurring is remote.

Target Organs: Central nervous system, lungs, kidneys and spleen.

SECTION 12 – ECOLOGICAL INFORMATION

No specific toxicology data on this product is available. When used as indicated, no adverse environmental effects are foreseen. Avoid contaminating waterways.

Persistence/Degradability: Not readily biodegradable; slowly biodegradable in aerobic conditions.

Mobility in Soil: Not soluble in water.

SECTION 13 – DISPOSAL CONSIDERATIONS

Do not incinerate or puncture aerosol cans. If aerosol can develops a leak, allow to fully discharge before disposal. Prevent disposal in sewers and waterways. Normally suitable for disposal at approved land waste site, but review Commonwealth, State and local government requirements prior to disposal.

SECTION 14 – TRANSPORT INFORMATION

UN Number: UN1950

UN Proper Shipping Name: Aerosol

Transport Hazard Class: ADG Class 2, no sub-risk.

Packaging Group: Not applicable.

Hazchem Code: 2Y

SECTION 15 - REGULATORY INFORMATION

Poisons Schedule: None allocated.

SECTION 16 – OTHER INFORMATION

Initial copy of 16-heading MSDS.

Since the user's working conditions are not known by the supplier, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations. The product must not be used for any purposes other than those specified in Section 1 without first obtaining written handling instructions. MANTEK assumes no responsibility for personal injury or property damage

caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such non-recommended use, storage or disposal of the product.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations. The information given on this safety data sheet must be regarded as a description of the safety requirements relating to our product and not a guarantee of its properties.