

# SAFETY DATA SHEET

## STAINLESS STEEL CLEANER & POLISH

### Section 1. Chemical product and company identification

**Product name** : STAINLESS STEEL CLEANER & POLISH  
**Recommended use and restrictions** : Metal Polish  
Use only for the purpose on the product label.

**Product dilution information** : Not applicable

**Supplier's information** : Ecolab Inc. Institutional Division  
370 N. Wabasha Street  
St. Paul, MN 55102  
1-800-352-5326

**Code** : 900096-03

**Date of issue** : **28 Feb 2013**

EMERGENCY HEALTH INFORMATION: 1-800-328-0026  
Outside United States and Canada CALL 1-651-222-5352 (in USA)

### Section 2. Hazards identification

**GHS Classification** : **Product AS SOLD**  
FLAMMABLE AEROSOLS. - Category 2  
GASES UNDER PRESSURE - Compressed gas  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Narcotic effects] - Category 3

#### GHS label elements

**Signal word** : Warning

**Symbol** : 

**Hazard statements** : Flammable aerosol.  
Contains gas under pressure; may explode if heated.  
May cause drowsiness and dizziness.

#### Precautionary statements

**Prevention** : Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Pressurized container: Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing vapor.

**Response** : IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.

**Storage** : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place.

#### **Product AT USE DILUTION**

Product is sold ready to use.

## Section 2. Hazards identification

**Disposal** : See section 13 for waste disposal information.  
**Other hazards** : None known.

## Section 3. Composition/information on ingredients

**Substance/mixture** : Mixture

### Product AS SOLD

Hazardous ingredients	Concentration Range (%)	CAS number
white mineral oil, petroleum	5 - 20	8042-47-5
BUTANE	5 - 20	106-97-8
PROPANE	1 - 5	74-98-6
solvent naphtha (petroleum), medium aliph.	1 - 5	64742-88-7

### Product AT USE DILUTION

Hazardous ingredients	Concentration Range (%)	CAS number
Product is sold ready to use.		

## Section 4. First aid measures

	Product AS SOLD	Product AT USE DILUTION
<b>Eye contact</b>	: No known effect after eye contact. Rinse with water for a few minutes.	Product is sold ready to use.
<b>Skin contact</b>	: No known effect after skin contact. Rinse with water for a few minutes.	
<b>Inhalation</b>	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if you feel unwell.	
<b>Ingestion</b>	: Get medical attention if symptoms occur.	
<b>Protection of first-aiders</b>	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.	
<b>Notes to physician</b>	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.	

See toxicological information (section 11)

## Section 5. Fire-fighting measures

### Product AS SOLD

**Suitable fire extinguishing media** : Use water spray, fog or foam.

**Specific hazards arising from the chemical** : Flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may create fire or explosion hazard.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide

**Specific fire-fighting methods** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** :

## Section 5. Fire-fighting measures

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

	<b>Product AS SOLD</b>	<b>Product AT USE DILUTION</b>
<b>Personal precautions</b>	: Use personal protective equipment as required.	Product is sold ready to use.
<b>Environmental precautions</b>	: Avoid contact of large amounts of spilled material and runoff with soil and surface waterways.	
<b>Methods for cleaning up</b>	: Use a water rinse for final clean-up.	

## Section 7. Handling and storage

	<b>Product AS SOLD</b>	<b>Product AT USE DILUTION</b>
<b>Handling</b>	: Store and use away from heat, sparks, open flame or any other ignition source. Liquid and vapor under pressure. Do not puncture, incinerate or store the container at temperatures above 49°C (120°F) or in direct sunlight. Use only with adequate ventilation. Wash thoroughly after handling.	Product is sold ready to use.
<b>Storage</b>	: Keep out of reach of children. Keep container tightly closed and sealed until ready for use. Keep container in a cool, well-ventilated area. Avoid all possible sources of ignition (spark or flame). Do not puncture or incinerate container. Store between the following temperatures: 5 and 45°C	

## Section 8. Exposure controls/personal protection

**Control parameters**

Ingredient name	Exposure limits
white mineral oil, petroleum	<b>ACGIH TLV (United States, 3/2012).</b> TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction <b>NIOSH REL (United States, 6/2009).</b> TWA: 5 mg/m <sup>3</sup> 10 hours. Form: Mist STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Mist <b>OSHA PEL (United States, 6/2010).</b> TWA: 5 mg/m <sup>3</sup> 8 hours.
BUTANE	<b>ACGIH TLV (United States, 3/2012).</b> TWA: 1000 ppm 8 hours. <b>NIOSH REL (United States, 6/2009).</b> TWA: 800 ppm 10 hours. TWA: 1900 mg/m <sup>3</sup> 10 hours.
PROPANE	<b>ACGIH TLV (United States, 3/2012).</b> TWA: 1000 ppm 8 hours. <b>OSHA PEL (United States, 6/2010).</b> TWA: 1800 mg/m <sup>3</sup> 8 hours. TWA: 1000 ppm 8 hours. <b>NIOSH REL (United States, 6/2009).</b> TWA: 1000 ppm 10 hours.

## Section 8. Exposure controls/personal protection

solvent naphtha (petroleum), medium aliph.

TWA: 1800 mg/m<sup>3</sup> 10 hours.  
**OSHA PEL (United States, 6/2010).**  
 TWA: 100 ppm 8 hours.  
 TWA: 400 mg/m<sup>3</sup> 8 hours.

### Product AS SOLD

**Appropriate engineering controls** : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

### Personal protection

**Eye protection** : No protective equipment is needed under normal use conditions.

**Hand protection** : No protective equipment is needed under normal use conditions.

**Skin protection** : No protective equipment is needed under normal use conditions.

**Respiratory protection** : A respirator is not needed under normal and intended conditions of product use.

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.

### Product AT USE DILUTION

Product is sold ready to use.

## Section 9. Physical and chemical properties

### Product AS SOLD

**Physical state** : Aerosol

**Color** : White

**Odor** : citrus

**pH** : Not applicable

**Flash point** : Not applicable

**Explosion limits** : Lower: 1.8%  
Upper: 9.5%

**Flammability (solid, gas)** : Not available.

**Melting point** : Not available.

**Boiling point** : >100°C (>212°F)

**Evaporation rate (butyl acetate = 1)** : Not available.

**Vapor pressure** : Not available.

**Vapor density** : Not available.

**Relative density** : 0.951 to 0.951 (Water = 1)

**Solubility** : Soluble in the following materials: cold water and hot water.

**Partition coefficient: n-octanol/water** : Not available.

### Product AT USE DILUTION

Product is sold ready to use.

## Section 9. Physical and chemical properties

Auto-ignition temperature : Not available.  
 Decomposition temperature : Not available.  
 Odor threshold : Not available.  
 Viscosity : Not available.

### Aerosol product

Type of aerosol : Spray  
 Heat of combustion : 6.246 kJ/g  
 Ignition distance : 0 cm  
 Flame height : Not available.  
 Flame duration : Not available.

## Section 10. Stability and reactivity

### Product AS SOLD

Stability : The product is stable.  
 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.  
 Conditions to avoid : Avoid all possible sources of ignition (spark or flame).  
 Materials to avoid : Highly reactive or incompatible with the following materials: oxidizing materials.  
 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

Route of exposure : Skin contact, Eye contact, Inhalation, Ingestion

### Product AS SOLD

#### Symptoms

Eye contact : No specific data.  
 Skin contact : No specific data.  
 Inhalation : Adverse symptoms may include the following:  
 respiratory tract irritation  
 coughing  
 nausea or vomiting  
 headache  
 drowsiness/fatigue  
 dizziness/vertigo  
 unconsciousness  
 Ingestion : No specific data.

#### Acute toxicity

Eye contact : No known significant effects or critical hazards.  
 Skin contact : No known significant effects or critical hazards.  
 Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness.  
 Ingestion : Can cause central nervous system (CNS) depression.

### Product AT USE DILUTION

Product is sold ready to use.

#### Toxicity data

Product/ingredient name	Result	Species	Dose
-------------------------	--------	---------	------

## Section 11. Toxicological information

white mineral oil, petroleum	LC50 Inhalation Dusts and mists	Rat	>5.2 mg/l
	LD50 Dermal	Rabbit	>2000 mg/kg
	LD50 Oral	Rat	>5000 mg/kg
butane	LC50 Inhalation Gas.	Rat	280000 ppm
solvent naphtha (petroleum), medium aliph.	LD50 Dermal	Rabbit	>2000 mg/kg
	LD50 Oral	Rat	>5000 mg/kg

### Chronic toxicity

<b>Carcinogenicity</b>	: No known significant effects or critical hazards.
<b>Mutagenicity</b>	: No known significant effects or critical hazards.
<b>Teratogenicity</b>	: No known significant effects or critical hazards.
<b>Developmental effects</b>	: No known significant effects or critical hazards.
<b>Fertility effects</b>	: No known significant effects or critical hazards.

## Section 12. Ecological information

### Product AS SOLD

**Ecotoxicity** : No known significant effects or critical hazards.

### Aquatic and terrestrial toxicity

Product/ingredient name	Result	Species	Exposure
white mineral oil, petroleum	Acute LC50 <100 mg/l	Fish	96 hours
butane	Acute LC50 22.03 mg/l	Fish	96 hours
solvent naphtha (petroleum), medium aliph.	Acute LC50 800 mg/l	Fish	96 hours

**Other adverse effects** : No known significant effects or critical hazards.

## Section 13. Disposal considerations

### Product AS SOLD

**Disposal methods** : Avoid disposal. Attempt to use product completely in accordance with intended use. Disposal should be in accordance with applicable regional, national and local laws and regulations. Do not puncture or incinerate container. Discard empty container in trash.

**RCRA classification** : Unused product is D001 (Ignitable)

### Product AT USE DILUTION

Product is sold ready to use.

## Section 14. Transport information

Certain shipping modes or package sizes may have exceptions from the transport regulations. The classification provided may not reflect those exceptions and may not apply to all shipping modes or package sizes.

### DOT

<b>DOT Classification</b>	UN1950
<b>DOT Proper shipping name</b>	Aerosols
<b>Class</b>	2.1
<b>Packing group</b>	-

### IMO/IMDG

<b>IMO/IMDG Classification</b>	UN1950
<b>IMO/IMDG Proper shipping name</b>	AEROSOLS
<b>Class</b>	2.1
<b>Packing group</b>	-

For transport in bulk, see shipping documents for specific transportation information.

